



A Certified MBE Company Delaware Industrial Park. 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

CERTIFICATE OF PLM ANAL

Page 1 of 5

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

4/22/2010

Sampling Data

BLI Project#: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTLB

Date Sampled: 4/7/10 Sampled By: Date Analyzed:

CLIENT 4/19/10

Samp	ole ID	Client-S	Supplied D	ata	Analytic	al Data	Re	eported Results	
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	mponents
640038	R-50	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
640039	R-179	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
640040	NR-75	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
640041	R-169	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
640042	NR-9	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	<1 % Chrysotile	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: <u>battaenv@battaenv.com</u> E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 NVLAP #101032

Page 2 of 5

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

4/22/2010

Sampling Data

Project Name:

BLI Project #: L446705

EA ENGINEERING-WALK-IN-1462309-NTLB

Sampled By: Date Analyzed:

Date Sampled:

CLIENT 4/19/10

4/6/10

Sample ID		Client-S	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
640043	R-35	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
	····	NTI D DODT	<u> </u>				98 % Non-fibrous		
640044	R-206	NTLB-PORT DEPOSIT	SOIL	· N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		g
640045	R-226	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	2 % Cellulose	ΝA	Non- Asbestos Containing
							98 % Non-fibrous		••••••
640046	R-19	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos
							98 % Non-fibrous		Containing
640047 R-	R-5	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark. Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

CERTIFICATE OF PLM ANALYSIS

Page 3 of 5

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date: Date Sampled:

4/22/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTLB

Sampled By: Date Analyzed:

CLIENT 4/20/10

4/8/10

Samp	ole ID	Client-S	Supplied D	ata	Analytic	al Data	Reported Results		
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	omponents
640049	NR-7	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	5 % Cellulose 95 % Non-fibrous	NA	Non- Asbestos Containing
640049	R-209	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
640050	R-181	NTLB-PORT DEPOSIT	SOIL	N/A	Fìrm	TAN	<1 % Cellulose	NA	Non- Asbestos Containing
640051	R-142	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
640052	R-178	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3% Cellulose 97% Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark. Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 4 of 5

CERTIFICATE OF PLM ANAL

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

4/22/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTLB

Date Sampled:

4/7/10

Sampled By: Date Analyzed:

CLIENT 4/20/10

Samp	ole ID	Client-S	Supplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents	
640053	R-159	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	GRAY	3 % Cellulose	<1 % Chrysotile	Non- Asbestos Containing	
640054	R-201	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	2 % Cellulose	2 % Chrysotile	Asbestos Containing	
							96 % Non-fibrous		-	
640055	R-166	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	<1 % Chrysotile	Non- Asbestos Containing	
640056	R-24	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing	
640057	R-190	NTLB-PORT DEPOSIT	ŞOIL	N/A	Firm	GRAY	3 % Cellulose	NA	Non- Asbestos Containing	

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment. Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three

samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

CERTIFICATE OF PLM ANALYSIS

Page 5 of 5

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

4/22/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTLB

Date Sampled: Sampled By:

4/7/10 CLIENT

Date Analyzed:

4/22/10

Sam	ple ID	Client-S	Supplied D	ata	Analytic	al Data	Reported Results		
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
640058	NR-81	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	TAN	<1% Cellulose	NA	Non- Asbestos Containing
640059	NR-82	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	RED	3 % Cellulose	NA	Non- Asbestos Containing
640060	R-31	NTLB-PORT DEPOSIT	SOIL	N/A	Firm	TAN	<1 % Cellulose	NA	Non- Asbestos Containing
640061 ⁻	R-223	NTLB-PORT DEPOSIT	SOIL	N/A Firm 2% RED		2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing	

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.

ge d

CHAIN OF CUSTODY



A Certified MBE Company

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com NVIAD NVLAP # 101032

AIHA

AIHA/NLLAP # 100448

EPA Lab#: DE004

Customer Bi	illing Informati	ion #	(10 5-110	Shipping Infor	mation		Turn	<u>Around</u>	Time (TAT)		Other TAT Re	annet :
		Tel:	(10-771-46C)		<u>M</u>	licroscopy		<u>Chemistr</u>	4	Other IAI IV	equest.
				□ Picked up by	BLI		Immediate		☐ 24 Hrs			
Customer Nam	ne: E7A	Extreenh	<u> </u>	Delivered by C			24 Hrs		☐ 48 Hrs			
Billing Address		aloun Cir		Shipped by Cu	ustomer		72 Hrs		☐ 72 Hrs	İ		
Billing Address	s 2: 50	ars, MD	てはらこ			Ø	5 Days		□ 5-7 Days	Lab Pr	oject#: عاد	46705
Send Results			10-329-5114	Project Name:		سيبسا د ۸	-B			 Client P	oject#: <u>24</u> Project#: VU	730
E-mail: (b) (4	(Peace	est con Fax: 4	10-771-4704	Project Location	1:	Fir		51J-				1.
BLI Use Only	Sample ID #	Sample Loc	ation/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analy	tical Type/Method	Results	Date of Analysis	Analyst
W10038	2.50	NTCBI	50:1	4/7/10			Soil	A:	>bestos	NAO	4/2/9/	o
039	R-179		1	417110)	NAO		
040	NR-075			4/7/10						WAO		
140	R-169			4/7/10						MAD		
042	NR-9			41748						4(% di	89	
043	R-35			416110						IVAO		
०५५	R-206			4/6/10						NAD		
045	R-226			4/5/10					·	NAO		
046	R-19	·		1412						NAD		
ar 047	2-5			415/103			V		V	NAD	V	
Sample Relinq		(4)	Date:		Time:	1100		Use Onl	у	Meth	od of Paymen	t
Sample Receiv		- · — <u>.</u> - · - —	Date:	4/12/10	Time:	13-5C) Are s	•	epted? If not, please ex	oplain 🔲 Ca	ash Cashier:	
Sample Reling	·		Date:				below		_		sa/Master Card/Disc	over
Sample Receiv	<u> </u>		Date:		Time:			es 🔲 N		n Ice Mo	oney Order	
Customer Spe	ecial Request/Co	omments (if applic	able):				Expla	nation/Com	ement;	1-	rchase Order#	
										☐ Ch		
											ice/Quote: ayment:	
										Other:	ayment.	
BLI Use Only							For	nat of Re	esuits Reported:		lus customer COC	
	Logged	in by: (b) (4)	Date of Logi	in: <u>4/13/co</u>	Time:	9205			ustomer COC and BLI			
Lab Comment		· -	9					rted by:		Date:	Time:	
!							Via:	☐ Fax	☐ Phone	E-mail:		
				•				'erbal	Person Contacted:			

CHAIN OF CUSTODY

battaLABORATORIES

A Certified MBE Company

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com NVIAD NVLAP # 101032
AIHA
AIHA
PPA Lab#: DF004

		morninonic onic	70 1002 1011 (002	7 101 0010 1 030 (0	,	• •	TTOOT TITEPIN	11 11 11 11 Daile	3111100111		El / Labii. DE	-00-1
Customer F	Billing Informat	ion		Shipping Infor	mation	,		Around Tin	ne (TAT)		Other TAT Re	auget :
oustomer t		Tel:	410-329-514	Simpping anor	mation	<u> N</u>	licroscopy		<u>Chemistr</u>	ן ע	Other IAI Re	quest.
				☐ Picked up by	BLI		Immediate		24 Hrs			
Customer Na	me:	ve Siran	2 EABhleain	Delivered by 0	Customer		24 Hrs		□ 48 Hrs	•	· · · · · · · · · · · · · · · · · · ·	
Billing Addres	ss 1: 145 La	weten Civ		Shipped by Cu	ustomer		72 Hrs		☐ 72 Hrs			
Billing Addres			21152	., .		1 20	5 Days		☐ 5-7 Day	s Lab F	roject#: کے بات	11.705
Send Results			410-329-5-114	Project Name:		1.5/	- /2			Client	Project #: 146	2 <i>2</i> 379
E-mail: (b) (4	()	-	410-771-4204	Project Location):	2.1	J- Degos	1 1			<u>v-ve</u>	، ترج
			 	Sample		Sample	7 0			-i	Date of	
BLI Use Only	Sample ID #	Sample	Location/Description	Date/Time	Volume	Area	Sample Type	Analytical	Type/Method	Results	Analysis	Analyst
640 048	NR-7	NTCB	10000 0000	4/8/10	150z	NR	Soi)	Prima	Asbesta	WAD	Hizdio	
1				418/10	1000		۱	N 2000	i	MAD	100010	
049	R-209	NTC	3/50:1	1315		R	 	···	 -	- '		
050	R-181			417110		R				NAD		
051	R-14Z			418110		R				NAO		
052	R-178			417110		R		,		CAN		
053	12-159			4/7/10		R				c(7. d)	YY) V	
254	R-201			417110		e				2%ch8		
	<i>(</i> 2)			0,500	<u></u>	R	 			-		
055	K-166			4/7/10						2lt.ch	ry	
056	R-24			41710		R				NAD		
+ 057	R-190	1 and	\mathcal{N}	417110 1055		R	4			NAD	<i>V</i>	
Sample Relin	quished by: (b)	(4)	Date:	4/10/10	Time:	1100	BLI	Jse Only	317	Met	hod of Payment	· .
Sample Rece			Date:	4/12/10	Time:	13450	Are sa	mples accepted	d? If not, please e	xplain 🔲	Cash Cashier:	
Sample Relin			Date:		Time:		below.			□ \	/isa/Master Card/Disc	over
Sample Rece	ived by:		Date:		Time:		FZ (Ye	es 🔲 No	☐ Received of	on Ice 🔲 l	Money Order	
Customer Sp	ecial Request/C	omments (if ap	plicable):				Explar	nation/Commen	t:		Purchase Order#	
											Check#	
							1 11				Price/Quote:	
											Payment:	
							▃▎▐└ੁ┈			jOthe		
BLI Use Only	, Logged	lin hye (b) (4)	Date of Log	in: 4(13/10	Timas	9:05			Its Reported: ner COC and BLI		plus customer COC	
Lab Commer		ini by.	Date of Log	<u>41131/9</u>	rime:	1.0°2		ils COC, custon led by:	Het OOC SUB REI	certificate Date	e; Time:	
	14.							Fax	☐ Phone	E-mail:	· · · · · · · · · · · · · · · · · · ·	
							□ V€		erson Contacted:			

CHAIN OF CUSTODY



A Certified MBE Company

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com NVLAP # 101032

AIHA


AI

Customer Billing Information	on .	Shipping Information	Turn A	round Time (TAT)	Other TAT Reques	ef ·
Customer Dining informatic	Tel: <u>410-329-5114</u>	ompring information	<u>Microscopy</u>	Chemistry	Other 171 Reques	J
*		□ Picked up by BLI	Immediate	□ 24 Hrs		
Customer Name: Dave	Straume EDE hileen	Delivered by Customer	□ 24 Hrs	□ 48 Hrs		
	oveten circle	Shipped by Customer	☐ 72 Hrs	□ 72 Hrs		
	cks, MD 21152		☑ 5 Days	□ 5-7 Days	Lab Project #: しょりょう	05
Send Results To: (b) (4)	Tel: 410-329-5114	Project Name:	NTCB	· · · · · · · · · · · · · · · · · · ·	Client Project #: 14 3620	7
E-mail: (b) (4)	Fax: 410.771-4204	Project Location:	Port Depos	A	· · · · · · · · · · · · · · · · · · ·	
BLI Use Only Sample ID #	Sample Location/Description	Sample Volume	Sample Sample Type	Analytical Type/Method	Analysis	alyst
640 058 NR -81	NTCB/50:1	917110	Soil	Asbestos	MAD 4/2410	
059 NR-82		417110	_		NAD	
060 R-31		4/16/10			NAO	
1-220		41542	 			ــــا
DOG R-223	1	41 5 10			NAD V	
* Per convers	solow with Karen Murdock	4/15/10. Analyze sa	401E R-226 001	once 3?		
	16M-1					
Sample Relinquished by: (b) (4		4/10/10 Time:	100 BLIL	lse Only	Method of Payment	
Sample Received by:i	Date:	4/12/10 Time:	15-50 Are sar	mples accepted? If not, please exp		
Sample Relinquished by:	Date:	Time:	below.		☐ Visa/Master Card/Discover	
Sample Received by:	Date:	Time:		s No Received on		
Customer Special Request/Co	mments (if applicable):		Explan	ation/Comment:	Purchase Order#	
					Check #	
					Unit Price/Quote: Total Payment:	
					Other:	
BLI Use Only			Form	at of Results Reported:	☐ This COC plus customer COC	
Logaed i	in by: (b) (4)	in: <u>4/13/10</u> Time:		is COC, customer COC and BLI ce		
Lab Comment:			Reporte		Date; Time:	
				-	E-mail:	
				rbal Person Contacted:		



Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



Page 1 of 6

CERTIFICATE OF PLM ANALYSIS

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

5/3/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTCB

Date Sampled: 4
Sampled By:

4/13/10 CLIENT

Date Analyzed:

CLIENT 5/3/10

Samp	ole ID	Client-S	upplied D	ata	Analytic	al Data	Reported Results		
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
641059	R-136	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97% Non-fibrous		
641060	R-149	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97% Non-fibrous		
641061	R-79	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	5% Cellulose	NA	Non- Asbestos Containing
		_					95 % Non-fibrous		
641062	R-89	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		Containing
641063	R-104	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	2% Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

(b) (4)

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark. DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF PL

Page 2 of 6

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

5/3/2010

Sampling Data

Project Name:

BLI Project #: L446705

EA ENGINEERING-WALK-IN-1462309-NTCB

4/12/10 Date Sampled: CLIENT Sampled By: Date Analyzed: 5/3/10

Samp	ole ID	Client-S	Supplied D	ata	Analytic	al Data	Re	ported Result	ts
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
641064	R-87	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
641065	NR-85	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
641066	NR-86	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	97% Non-fibrous 2% Cellulose	NA	Non- Asbestos Containing
							98% Non-fibrous		
641067	R-127	NTCB-PORT DEPOSIT	Soil	N/A	Firm	TAN	2% Cellulose	NA	Non- Asbestos Containing
							98% Non-fibrous		
641068	NR-74	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	2% Cellulose	NA	Non- Asbestos Containing
							98% Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.

batta



BATTA LABORATORIES, INC.

A Certified MBE Company
Delaware Industrial Park, 6 Garfield Way
Newark, DE 19713-5817
Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 AIHA A #100448 Environmental Laad a Industrial Hygiene See chelstop-org Work definition | NVLAP #101032

Report Date:

CERTIFICATE OF PLM ANALYSIS

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Page 3 of 6

5/3/2010

Sampling Data

BLI Project # : L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTCB

Date Sampled: 4/12/10

Sampled By: CLIENT

Date Analyzed: 4/27/10

Samp	ole ID	Client-S	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents
641069	R-121	NTCB-PORT DEPOSIT	Soil	N/A	Firm	TAN	5% Cellulose	NA	Non- Asbestos Containing
							95% Non-fibrous		
641070	R-140	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	<1% Chrysotile	Non- Asbestos Containing
							97% Non-fibrous		
641071	R-126	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		g
641072	R-115	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	<1% Cellulose	NA	Non- Asbestos Containing
							100% Non-fibrous		3
641073	R-132	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	<1% Cellulose	NA	Non- Asbestos Containing
							100% Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

(b) (4)

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark. DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 NVLAP #101032

Page 4 of 6

CERTIFICATE OF

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

5/3/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTCB

Date Sampled: Sampled By:

4/12/10 CLIENT

Date Analyzed: 5/3/10

Samp	ole ID	Client-S	Supplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents	
641074	R-161	NTCB-PORT DEPOSIT	Soil	N/A	Fìrm	TAN	2% Cellulose	NA	Non- Asbestos Containing	
							98% Non-fibrous			
641075	NR-78	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	5% Cellulose	<1 % Chrysotile	Non- Asbestos Containing	
							95% Non-fibrous		9	
641076	NR-63	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	5% Cellulose	NA	Non- Asbestos Containing	
		NTCB-PORT					95% INOR-TIDIOUS			
641077	NR-59	DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing	
							97% Non-fibrous		y	
641078	NR-68	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	2% Cellulose	NA	Non- Asbestos Containing	
							98% Non-fibrous			

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company
Delaware Industrial Park, 6 Garfield Way
Newark, DE 19713-5817
Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 Environmental Land a h.I.H.A. /NLLAP Environmental hypenn See shelspapen for couls with the property of the shelspapen for world with the shelspapen for the shelspapen for which the shelspapen for the shell and the shell as
4/9/10

CERTIFICATE OF PLM ANALYSIS

Page 5 of 6

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Sampled:

5/3/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTCB

Sampled By: CLIENT Date Analyzed: 5/3/10

Samp	ole ID	Client-S	Supplied D	ata	Analytic	al Data	Re	eported Resul	ts
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
641079	R-152	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	2% Cellulose	NA	Non- Asbestos Containing
641080	NR-76	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	2% Cellulose	NA	Non- Asbestos Containing
641081	R-172	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BŁACK	5% Cellulose	NA	Non- Asbestos Containing
641082	NR-57	NTCB-PORT DEPOSIT	Soil	N/A	Firm	TAN	3% Cellulose	NA	Non- Asbestos Containing
641083	NR-53	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose 97% Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

(b) (4)

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



A Certified MBE Company Delaware Industrial Park. 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF

Page 6 of 6

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date: Date Sampled:

5/3/2010

Sampling Data

Project Name:

BLI Project #: L446705

EA ENGINEERING-WALK-IN-1462309-NTCB

Sampled By: CLIENT Date Analyzed: 5/3/10

4/9/10

Sam	ole iD	Client-S	Supplied D	ata	Analytic	al Data	Re	ported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
641084	A-1	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		
641085	NR-83	NTCB-PORT DEPOSIT	Soil	N/A	Firm	RED	5% Cellulose	NA	Non- Asbestos Containing
							95% Non-fibrous		-
641086	R-100	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	2% Cellulose	NA	Non- Asbestos Containing
							98% Non-fibrous		
641087	R-150	NTCB-PORT DEPOSIT	Soil	N/A	Firm	TAN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		_
641088	NR-62	NTCB-PORT DEPOSIT	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97% Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.

A Certified MBE Company

CHAIN OF CUSTODY

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376, Fax: (302) 737-5764

E-mail: battaenv@battaenv.com

MVLAP # 101032 AIHA/NLLAP # 100448 EDA Lab#: DE004

Dedicated to	a Cleaner Env	/ironment Sind	ce 1982 Tel: (30	02) 737-3376 Fax: (30	02) 737-576	64	Web: http:/	/www.battae	nv.com		EPA Lab#: DI	E004
Customer B	Billing Informat	fion	***	Shipping Infor	mation			Around Tin			Other TAT Re	equest :
O aoioino. 2		Tel:	410-77-4950)			icroscopy		<u>Chemistry</u>	<i>L</i> '	Wile IN IN	equest.
	i - ^			☐ Picked up by		- #1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	Immediate		□ 24 Hrs			
Customer Nan		Chzines		Delivered by C			24 Hrs		48 Hrs	<u> </u>	A A	, 705
Billing Address		Loweten	arelo	☑ 8hipped by Cu	ustomer	1-	72 Hrs		☐ 72 Hrs		LAG	6705 16230
Billing Address			VD 51125				5 Days		☐ 5-7 Days		*******	16620
Send Results		el:				107	CB_			Client Pr	roject #:	
E-mail: (b) (4		ax:	: 410-771-4800	Project Location	1:	Por	4 Dep	15 051				
BLI Use Only	Sample ID #	Sample	Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type	1	Type/Method	Results	Date of Analysis	Analyst
641059	R-136	NTCB	50:1	4(13)10			501	Asia	estos	NAO	4/27/10	57
060	R-149	<u> </u>	1	4113110				<u> </u>	.	NAO		
061	R-79			4113110				1		NAD		
062	R-89			4112110						NAD	1_1_	
063	R-104			4112110					T	NAD		,
064	2-87			4112110					T	WAD		
065	NR-85		·	4)12110					<u> </u>	NAD		2.75
066	NR-86			4112/10						IVAD	7	
067	2-127	1		111210						NAO	5/3/10	
J 068	NR-74	11/2 hr		4112110			V			NAD		•
Sample Reling) (4)	Date:		Time:	1100		Use Only			od of Payment	
Sample Receiv			Date:	· I	Time:		Are sa		d? If not, please exp	,		
Sample Receive	·		Date: Date:	 	_Time: Time:			v. ∕es □ No	☐ Received on	_	a/Master Card/Disc ney Order	cover
· ·	ecial Request/C	omments (if ar			· · · · · · · · · · · · · · · · · · ·		 1/	nation/Comment			rchase Order#	
Oustoine: 5	20101 1104met==	Ollinoine (1. 4-1-	phonoic _j .					There is a second	,	Che		
								INVOICE	<u></u>	Unit Pric	ce/Quote:	
								(10 A - r		Total Pa	syment:	
BLI Use Only							- 		Its Reported:	Other:		
BLI USE Omy		d in by: $\c B V$	Date of Log	gin: 421/10	Time:	1252	i I		ner COC and BL1 o		JS Customer CCC	
Lab Comment			Date of Log	JIII		1002	—	rted by:	101 000 and 52. 5	Date:	Time:	:
								□ Fax	Phone	E-mail:		
				•			 	erbal Pe	erson Contacted:			

CHAIN OF CUSTODY

ศาสโลด NVI AP # 101032

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Dedicated to a Cleaner Environment Since 1982 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

10 0 Cara	144171 # 101002
AIHA A	AIHA/NLLAP # 100448
	EDA Lab#: DE004

Customer E	Billing Informat	ion Tel: 410-771-493	Shipping Information	NA:		Ound Time (TAT)	-,	Other TAT Re	quest :
		10110-171 173	☐ Picked up by BLI	1	icroscopy Immediate	Chemistry ☐ 24 Hrs			-
Customer Na	me: EA		☐ Delivered by Custome	4 4			· L		
Billing Addres		ensieering	Shipped by Customer	1	24 Hrs	48 Hrs		L496	75
Billing Addres		Weten Circle	Customer		72 Hrs	□ 72 Hrs		• •	
Send Result		Tel: 410-379-51	.t/ Danie at Names	, 1	5 Days	☐ 5-7 Days			6230
	4)	<u> </u>		<u> </u>	- 12		Client F	Project #:	
E-mail.		ax: 410-771-4204	Project Location:	rec	+ Depo	<u> </u>			
BLI Use Only	Sample ID #	Sample Location/Description	Sample Volume	Sample Area	Sample Type	Analytical Type/Method	Results	Date of Analysis	Analyst
641069	2-121	NTCB 1.5:1	4112110		So:1	Ashestos	NAD	5/3/1.	JT
070	R-140	<i>l</i>	4112110			1	MAD 4		
७७	R-126		4112110				NAD		
072	R.115		4/12/10				MAD		
A 3	R-132		4112/10				NAO		
074	12-161		4112110				NAD		
275	NR-78		4112110			<17.	NAD	chro	
076	NR-63		419110				MAD		
077	NR-59	, , , , , , ,	9 9 9 11 0 1350	-	1/		NAD		
J 878	NRUS	1 Par Va	पार्वा ।	1	- 		NAD	+ +	
Sample Relin	//-/	(4) Date:	4/17/10 Time:	1100	BLI Us	e Only		od of Payment	
Sample Rece	ived by:	Date:	Time:	7.00	—	ples accepted? If not, please exp		•	
Sample Reline	·	Date:	Time:		below.	, , , ,	☐ Vi	sa/Master Card/Disco	ver
Sample Recei		Date:	Time:		X Yes	☐ No ☐ Received on	Ice 🔲 M	oney Order	
Customer Sp	ecial Request/Co	omments (if applicable):			Explanati	on/Comment:	□ Pt	ırchase Order#	-
							☐ Ch		
					1 1 (4	JVDICE-	1	ice/Quote:	
							Total P Other:	ayment:	
BLI Use Only					Format	t of Results Reported:		alus customer COC	
_	Logged	in by:BH Date of Log	gin: 4/21/10 Time	: 1252	t I	COC, customer COC and BLI ce		145 545 541 541 545	
Lab Commen				<u></u>	Reported		Date:	Time:	l
					Via: □		E-mail:		
					☐ Verba	al Person Contacted:			

battaLABORATORIES

Dedicated to a Cleaner Environment Since 1982

CHAIN OF CUSTODY

Page 3 of 3

Delaware Industrial Park

6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764 E-mail: battaenv@battaenv.com Web: http://www.battaenv.com NVIAP # 101032



AIHA/NLLAP # 100448

EPA Lab#: DE004

Customer	Billing Informati	ion		Shipping Infor	mation		Turn A	Around Time (TAT)	Other TAT Request :		
	Dilling Informati	Tel:	410-771-492)	mauon	<u> </u>	licroscopy	<u>C</u>	<u>hemistry</u>		Other IAT IX	squest.
		_		☐ Picked up by	BLI		Immediate		24 Hrs	1		l
Customer Na	ame: 🗔	+ Encine	2000-	Delivered by C	Customer		24 Hrs		48 Hrs	·		
Billing Addre	ss 1:	Lovete		Shipped by Cu	ustomer		72.Hrs		72 Hrs		ردادا	623d),
Billing Addre	ss 2:		202153	• • •		i	5 Days		5-7 Days	Lab P	roject#: 14	623d
-	s To: (b) (4)		410-329-5114	Project Name:		<u> </u>	MCB				Project #:	<u> </u>
/ - \	(4)		410-771-4204	Project Location		On	+ Des	2007				
				Sample		Sample	- 1			· · · · · · · · · · · · · · · · · · ·	Date of	
BLI Use Only	Sample ID #	Sample	Location/Description	Date/Time	Volume	Area	Sample Type			Results	Analysis	Analyst
641079	R-152	NIC	-B/ Soil	49110			Sil	H520	5405	NAO	5/3/10	57
080	NR-76	····	/	4113110			1		<u> </u>	NAD		
180	12-172			4112110						IVAD		
082	WR-57			419110 1430						NAO		
083	NQ-53			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						MAD		
084	A-1			419110						NAO		
085	NQ.63			4/12/10						WAD		
086	R-166			49110					,	MAD		
087	R-150	1		41918			l		./	WAD	,	
V 088	NR-62	Th		419110						NAD	J	1
Sample Relir	quished by: (b)	(4)	Date:	411110	Time:	1100	BLI	Use Only	···············	Meti	od of Paymen	t
Sample Rece	· · · · · · · · · · · · · · · · · · ·	- V 1	Date:	*) 1	Time:		Are sa	amples accepted? If n	ot, please exp	olain 🔲 🤇	ash Cashier:	
Sample Relin			Date:		Time:		below			□ ∨	isa/Master Card/Disc	cover
Sample Rece			Date:		Time:		<u> </u>		Received on	lce 🗀 M	oney Order	
Customer S	pecial Request/Co	omments (if ap	plicable):				Explai	nation/Comment:		i—	urchase Order#	
										ı—	heck#	
			•				 	INVOICE		1	rice/Quote:	
								-		Other	·	
BLI Use Onl	y						Form	nat of Results F	teported:	☐ This COC	plus customer COC	
•••		in by: Ts	Date of Log	in: 4/2/10	Time:	1252	i I	his COC, customer C	-			
Lab Comme								ted by:		Date	: Time:	
										E-mail:		
							_ □ ∨	erbal Person	Contacted:			





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark. DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF

Page 1 of 6

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date: Date Sampled:

5/25/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN-1462309-NTCB

Sampled By: CLIENT Date Analyzed:

5/10/10

4/9/10

Samı	ple ID	Client-S	upplied D	ata	Analyti	cal Data	Re	ported Results	3
Lab Sample#	Client Sample #	Sample Location	Material Type	Eriable?		Color	Non- Asbestiform Components	Asbestiform Component	
641089	NR-69	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	BLACK BROWN WHITE	3% Cellulose 97% Non-fibrous	NA	Non- Asbestos Containing
641090	R-138	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	BLACK BROWN WHITE	2 % Cellulose 2 % Fb-Glass 96 % Non-fibrous	NA	Non- Asbestos Containing
641091	NR-71	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	VARIOUS	10 % Cellulose 2 % Fb-Glass 88 % Non-fibrous	NA	Non- Asbestos Containing
641092	R-107	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	VARIOUS	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
641093	R-92	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	BLACK TAN WHITE	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

DANIEL PIERCE

REVIEWED BY:

* This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.


Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way

DE 19713-5817 Newark. Tel. (302) 737-3376 Fax (302) 737-5764



CERTIFICATE OF PLM

Report Date:

CLIENT

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Date Sampled: 4/15/10

5/25/2010

Page 2 of 6

Sampling Data BLI Project #:

Project Name:

L446705

EA ENGINEERING-WALK-IN-1462309-NTCB

Sampled By:

Date Analyzed: 5/10/10

Samı	ple ID	Client-S	upplied D	ata	Analyti	cal Data	Re	eported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
641094	NR-64	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	VARIOUS	10 % Cellulose 90 % Non-fibrous	NA	Non- Asbestos Containing
641095	R-147	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
641096	R-155	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2% Cellulose 98% Non-fibrous	NA	Non- Asbestos Containing
641097	NR-18	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	<1% Cellulose	NA	Non- Asbestos Containing
641098	NR-20	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	<1 % Cellulose	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^t This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

* Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three

samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way

DE 19713-5817 Newark. Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF PLM ANAL

Page 3 of 6

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

5/25/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN-1462309-NTCB

Date Sampled: Sampled By: CLIENT

4/14/10

Date Analyzed: 5/11/10

Samp	ole ID	Client-S	upplied D	ata	Analyti	cal Data	Re	eported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	omponents
641099	NR-49	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	BLACK BROWN WHITE	5% Cellulose 95% Non-fibrous	NA	Non- Asbestos Containing
641100	R-133	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	BLACK BROWN WHITE	5% Cellulose 95% Non-fibrous	NA	Non- Asbestos Containing
641101	R-129	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	TAN GRAY	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
641102	R-196	PORT DEPOSIT- NTCB	Soil	N/A	Firm Fibrous	BLACK BROWN WHITE	5 % Cellulose 95 % Non-fibrous	NA	Non- Asbestos Containing
641103	R-144	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

REVIEWED BY:

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles Defininitive results can be obtained by TEM analysis.

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.


^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.



Delaware Industrial Park, 6 Garfield Way Newark. DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF PLM ANAL

Page 4 of 6

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

5/25/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309-NTCB

Date Sampled: Sampled By:

4/14/10 CLIENT

Date Analyzed:

5/21/10

Samı	ple ID	Client-S	upplied D	ata	Analytic	cal Data	Re	ported Results	
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents
641104	R-125	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	<1 % Cellulose	NA	Non- Asbestos Containing
641105	NR-30	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
641106	NR-48	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
641107	NR-39	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2% Cellulose 98% Non-fibrous	NA	Non- Asbestos Containing
641108	NR-36	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

REVIEWED BY:

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.






A Certified MBE Company
Delaware Industrial Park, 6 Garfield Way

Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF PLM ANALYSIS

Report Date:

Page 5 of 6 5/25/2010

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Date Sampled:

Sampled By:

4/15/10

CLIENT

Sampling Data

BLI Project # :
Project Name:

L446705

L440703

EA ENGINEERING-WALK-IN-1462309-NTCB

Date Analyzed: 5/21/10

Sam	ole ID	Client-S	upplied D	ata	Analytic	cal Data	Re	eported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
641109	R-81	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
641110	R-69	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	<1 % Cellulose	NA	Non- Asbestos Containing
641111	R-97	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
641112	R-72	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2% Cellulose 98% Non-fibrous	NA	Non- Asbestos Containing
641113	R-94	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

(b) (4)

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles.

Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way

DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Report Date:

Page 6 of 6

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Date Sampled:

Sampled By:

5/25/2010

4/14/10

CLIENT

Sampling Data

BLI Project #: L446705 **Project Name:**

EA ENGINEERING-WALK-IN-1462309-NTCB

Date Analyzed: 5/21/10

Samp	ole ID	Client-S	upplied D	ata	Analytic	cal Data	Re	eported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
641114	NR-47	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	<1% Cellulose	NA	Non- Asbestos Containing
		PORT DEPOSIT-	Call				100 % Non-fibrous		
641115	NR-23	NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
er in the second							98 % Non-fibrous		elyptic en literation
641116	R-96	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.

battaLABORATORIES

Dedicated to a Cleaner Environment Since 1982

CHAIN OF CUSTODY

Page 1 of 3

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com NVLAP # 101032

AIHA/NLLAP # 100448

EPA Lab#: DE004

Customer F	Billing Information			Shipping Inforr	nation	DOCUMENTS.	Turn A	round Tir	ne (TAT)		Other TAT De	
Oustoiner L	Jimig imormati	Tel:	410-771-4950	Shipping mion	iiation	<u>M</u>	licroscopy		Chemistry		Other TAT Re	equest:
	. ^			☐ Picked up by	BLI		Immediate		□ 24 Hrs			
Customer Na	me: ZH	Engineer	ine	Delivered by C	ustomer		24 Hrs		☐ 48 Hrs			
Billing Addres		coveren		Shipped by Cu	stomer		72 Hrs		□ 72 Hrs	-		46705
Billing Addres	ss 2: \S	erks m	D 21152			O	5 Days		□ 5-7 Days	Lab Pr	oject #:) ५(02309
Send Results	s To: <mark>(b) (4)</mark>	Tel:	410-329-514	Project Name:		NTO	LB			Client P	roject #:	
E-mail: (b) (4	4)	Fax:	410-771-4204	Project Location	:	Part	-Depos	, 'A			1. The state of th	
BLI Use Only	Sample ID #	Sample	Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type		l Type/Method	Results	Date of Analysis	Analyst
	NR-69	NTCF	3 15001	1000			Suil	A ₇	Shostes	NAO	5/10/19	DP
	R-138			49110				HAZIMARA ESSANAS ANALYSIS ANALYSIS ANALYSIS ANA		MAD		
	NE-71			4/13/16						MAD		
	R-107			4113110						MAO	U.	
	R-92			14114110						MAD	5/2/1/9	24
1 () () () () () () () () () (NR-64			4115/10						Man		1
	R-147			4114110						uny		57
	R-155			4,112110						MAD		
	NR-18	2		4114110						WAD	1 1	
	NR-20 A	1 Phl	1 W	4113116					V	NAC		T.
Sample Relin	/	(4)	Date:	4/17/10	Time:	1100		Use Only			nod of Paymer	
Sample Rece Sample Relir			Date:		Time:		Are s		ed? If not, please ex	•	Cash Cashier: Sa/Master Card/Dis	
Sample Rece			Date:		Time:		— 🖂 Y	es 🔲 No	☐ Received or		foney Order	
Customer S	pecial Request/C	omments (if a	pplicable):				Expla	nation/Comme	ent:	70 P	urchase Order#	
										1	heck#	
								INVI	NCE		Price/Quote: Payment:	
										Other		
BLI Use Onl				>>		1226			ults Reported:		plus customer CO	>
l ab C		I in by: 413	기년 Date of Lo	gin: BH	Time	: 1304			omer COC and BLI			
Lab Comme	ent:						1 1 .	rted by:	☐ Phone	Date E-mail:	e: Time	ə:
							1 1	/erbal	Person Contacted:			

CHAIN OF CUSTODY

Page 2 of 3

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

MV(AP NVLAP # 101032 AIHA/NLLAP # 100448

EPA Lab#: DE004

Customer Ri	illing Information			Shipping Inform	nation		Turn A	round Ti	me (TAT)		74 - TAT D	
oustoniei Di	illing illioi matioi	Tel:	410-771-490	Shipping intori	nauon	<u>M</u>	licroscopy		Chemistry		Other TAT Re	quest :
				☐ Picked up by	Section 1.		Immediate		☐ 24 Hrs			
Customer Nan		nchee	£M5	Delivered by C			24 Hrs		☐ 48 Hrs			
Billing Address	s 1: 58 (s	5 Core		Shipped by Cu	stomer		72 Hrs		☐ 72 Hrs		Leteth	,7105
Billing Address		KS W				Ø	5 Days		☐ 5-7 Days	Lab Pro	oject #: ડિંબિડિ	,2309
Send Results		Tel:	410-329-511	YProject Name:			HCB		-	Client P	roject #:	,,,,,
E-mail: <mark>(b) (4</mark>	1)	رFax:	10-771-470	Project Location		Po	rt Dep	osit				
BLI Use Only	Sample ID #	Sample	Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analytic	al Type/Method	Results	Date of Analysis	Analyst
	NR-49	NTCE	3/50:1	4114110	***************************************		Soil	A	bestes	NAD	Thello	DP
	12-133			4/11/10				¥	Ţ	WAD		
	12-129			4115110	***************************************					WAD		
	R-194			4 115710						MAD		V
	R-144			4114110				'		NAD	5/21/10	- SH2
	R-125			4114/10						WAD		DEX
	NR-30			4)15/10						WAD	10%	57
	NE-48			411416						WAD		
	NR-39		\ \	पंडिंड					_ //	MAD		
	NR-360 X	M		411210			TU		V	NRD		1
Sample Relin		4)	Date:	4/17/10	Time:	1100	BLI	Use Only			nod of Paymer	
Sample Rece Sample Relin		/-	Date:	, ,	Time: Time:		Are so		oted? If not, please ex	•	ash Cashier: isa/Master Card/Dis	
Sample Rece			Date:		Time:			es □ No	☐ Received o		loney Order	cover
	pecial Request/Co	mments (if	applicable):				Expla	nation/Comm	nent:	P	urchase Order#	
											heck#	
								MYO	Œ	1	Price/Quote:Payment:	
										Other		
BLI Use Only	у			.L. 1.					sults Reported:		plus customer CO	3.
	Logged i	n by: §	Date of Lo	ogin: 4210	Time	1364			stomer COC and BLI			
Lab Comme	nt:							orted by:	☐ Phone	Date E-mail:	e: Time	3 :
							1 1	/erbal	Person Contacted:			

CHAIN OF CUSTODY

Page $\stackrel{>}{>}$ of $\stackrel{>}{<}$

NV(A) NVLAP#101032

AIHA/NLLAP # 100448

EPA Lab#: DE004

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

Customer B	illing Informati	on Tel:	6110-771-4950	Shipping Infor		,	licroscopy Immediate	Chemistro	<u>/</u> Ot	her TAT Re	quest :
Customer Nan	ne: FA	Enghos	CÍD.	☐ Delivered by C	ustomer		24 Hrs	□ 48 Hrs			······································
Billing Address	s 1:	LOVOtex	Circle	Shipped by Cu	ıstomer		72 Hrs	□ 72 Hrs		الحلوا	16705
Billing Address	s 2:	crks, W	15 21152			口	5 Days	□ 5-7 Day	Lab Proj	ect#:	6730
Send Results	To: (b) (4)	Tel:	410-329-511	→ Project Name:		17	TCB		Client Pro	-	
E-mail: (b) (4	4)	Fax:	410-771-4204	Project Location	n:	Port	- Depos	it		***	
BLI Use Only	Sample ID #	Sample I	Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analytical Type/Method	Results	Date of Analysis	Analyst
	R-81	NTCE	3/50:1	41/3/19			50.)	Ashertos	NAO	5/21/10	51
	R-69			4/15/10					MAD		(
	Ran			4/19/19					NAD		
	R-72			4/15/10					MAD		
	12.94			4114110		<u> </u>			IVAD		
la l	NR-47			4114110					NAD		
	NR-23			4115110					MAD		
	12.96			4115110					MAD		
		1 0							NAA-	st 1.	
	(b) (4)					1 1	Y	NAD		1
Sample Relin	quished by:		Date:	4/17/10	Time:	1100		Use Only		d of Paymen	
Sample Rece			Date:	· u	Time:		Are sa	amples accepted? If not, please		h Cashier: /Master Card/Dis	
Sample Relin Sample Rece			Date:		Time:			es □ No □ Received		iriwaster Card/Dis iey Order	cover
Land History I. S.	pecial Request/C	`ommonte (if ar	-					nation/Comment:		chase Order#	
Customer of	peciai Nequesuc	oniments (ii a	эрпсаые).						☐ Che		
								INVOICE	Unit Pric	e/Quote:	
								11410100	Total Pa	yment:	
									Other:		
BLI Use Only					· · · · · ·	- 1		mat of Results Reported		us customer COC	;
		d in by:	Date of Lo	gin: 42/10	Time	1304		his COC, customer COC and Bl		T !	
Lab Comme	nt:						1 1	rted by:	Date:	Time):
							1 1	/erbal Person Contacted			
			<u> A la directa de la barecaria.</u>								



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP AIHA #100448 NVLAP #101032

Page 1 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project #: L446705 Project Name:

EA ENGINEERING-WALK-IN

Date Sampled: Sampled By:

5/26/10 CLIENT

Date Analyzed: 8/10/10

Sam	ole ID	Client-S	upplied D	ata	Analytic	al Data	Re	eported Resul	ts
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
648387	TG10-14	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648388	F-69	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose	NA	Non- Asbestos Containing
648389	F-65	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	95 % Non-fibrous 3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
648390	TG4-6	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
648391	F-8	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 TED LABOR A.I.H.A. /NLLAP AIHA

#100448

NVLAP #101032

Page 2 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

Date Sampled: Sampled By:

5/27/10 CLIENT

Date Analyzed:

8/10/10

Sam	ple ID	Client-S	upplied D	ata	Analytic	al Data	Re	ported Result	s
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
648392	TG12-2	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose	NA	Non- Asbestos Containing
<u> </u>		PORT DEPOSIT-					95 % Non-fibrous	··	
648393	TG10-9	NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose	NA	Non- Asbestos Containing
							95 % Non-fibrous		3
648394	F-40	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous	-	
648395	F-47	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		Containing
648396	TG8-14	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		

Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 TED LABOR A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 3 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN

Date Sampled: Sampled By:

5/26/10 CLIENT

Date Analyzed:

8/10/10

Sam	ple ID	Client-S	upplied Da	ata	Analytic	al Data	Re	ported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
648397	TG8-8	PORT DEPOSIT- NTCB	Soil	Ň/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648398	TG9-2	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648399	F-76	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
648400	F-30	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
648401	F-21	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2% Cellulose 98% Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 4 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Sampled:

8/12/2010

Sampling Data

BLI Project#: L446705

Project Name: EA ENGINEERING-WALK-IN

Sampled By: Date Analyzed: 8/10/10

5/26/10 CLIENT

Sam	ole ID	Client-S	upplied D	ata	Analytic	al Data	Re	ported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
648402	F-51	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
648403	F-58	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648404	TG8-9	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	, NA	Non- Asbestos Containing
648405	TG4-14	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648406	TG4-11	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose 95% Non-fibrous	NA	Non- Asbestos Containing

Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.







A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark; Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 5 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Sampled:

Date Analyzed:

8/12/2010

Sampling Data

BLI Project#: L446705

Project Name: EA ENGINEERING-WALK-IN

Sampled By: CLIENT

5/26/10 8/10/10

Sam	ple ID	Client-S	upplied D	ata	Analytic	al Data	Re	eported Result	s
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
648407	TG8-5	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
		505555555					97 % Non-fibrous		
648408	AOC1A(689) 3-02	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Celluiose	NA	Non- Asbestos Containing
							98 % Non-fibrous		g
648409	AOC1C-8	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		_
648410	AOC1C-21	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		g
648411	AOC1C-4	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose	NA	Non- Asbestos Containing
							95 % Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 TEO LAPOR A.I.H.A. /NLLAP AHA #100448 NVLAP #101032

Page 6 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

Date Sampled: Sampled By:

5/14/10 CLIENT

Date Analyzed: 8/10/10

Sam	ple ID	Client-S	upplied Da	ata	Analytic	al Data	Re	eported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	Components
648412	AOC45A-58	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648413	AOC45A-39	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
648414	AOC45A-33	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA .	Non- Asbestos Containing
648415	AOC45A-25	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	97 % Non-fibrous 3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
648416	AOC45A-76	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA .	Non- Asbestos Containing

Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

Defininitive results can be obtained by TEM analysis.

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment. Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three

samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination. Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: <u>battaenv@battaenv.com</u>

E.P.A. LAB ID # DE 004 TEO LABOR A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 7 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Sampled:

8/12/2010

Non-

Asbestos Containing

NΑ

Sampling Data

BLI Project#: L446705

Sampled By:

5/12/10 CLIENT

Project N	Name: EA	A ENGINEERING-	WALK-IN				Date	Analyzed: 8/10	/10
Sam	ple ID	Client-S	upplied D	ata	Analytic	al Data	R	eported Results	
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents
648417	AOC3-23	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing
648418	AOC14-2	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2% Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		
648419	AOC14-3	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	<1 % Chrysotile	Non- Asbestos Containing
648420	AOC35-26	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	98 % Non-fibrous 3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

Firm

BROWN

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

648421 AOC35-21

Defininitive results can be obtained by TEM analysis.

PORT DEPOSIT-

NTCB

REVIEWED BY:

3 % Cellulose

97 % Non-fibrous

Soil

N/A

This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination. Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 TED LABOR A.I.H.A. /NLLAP AHA #100448 **NVLAP** #101032

Page 8 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

Date Sampled: Sampled By:

5/18/10 CLIENT

Date Analyzed:

8/10/10

Sam	ple ID	Client-S	upplied Da	ata	Analytic	al Data	Re	ported Resul	ts
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
648422	AOC35-30	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
648423	AOC35-32	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		
648424	AOC35-27	PORT DEPOSIT- NTCB	Soìl	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
		PORT DEPOSIT-					98 % Non-fibrous		
648426	AOC35-11	NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		Oomaning
648427	TG3-17	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containin
							98 % Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE-2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park. 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Page 9 of 17

Date Sampled: Sampled By:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN

Date Analyzed: 8/10/10

CLIENT

5/25/10

Samp	ole ID	Client-S	upplied Da	ata	Analytic	al Data	Re	eported Results	•
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	mponents
648428	TG7-5	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
648429	TG5-9	PORT DEPOSIT- NTCB	Sail	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
648430	AOC3-38	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
648431	AOC3-49	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	98 % Non-fibrous 2 % Cellulose 98 % Non-fibrous	<1 % Chrysotile	Non- Asbestos Containing
648432	AOC3-29	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	3 % Cellulose	<1 % Chrysotile	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

A Certified MBE Company
Delaware Industrial Park, 6 Garfield Way
Newark, DE 19713-5817
Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004

AIHA A.I.H.A. /NLLAP

Environmental Lend a Industrial Hygiene See Absigup, org of off details

NVLAP #101032

CERTIFICATE OF PLM ANALYSIS

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Page 10 of 17

8/12/2010

_ . . .

5/11/10

CLIENT

Date Sampled: Sampled By:

Date Analyzed: 8/10/10

Report Date:

Sample ID		Client-Supplied Data			Analytical Data		Reported Results		
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	omponents
648433	AOC3-11	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
648434	AOC3-6	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		
648435	AOC3-34	PORT DEPOSIT- NTCB	Soil	N/A	Firm	GRAY	3% Cellulose	NA	Non- Asbestos Containing
648436	AOC3-16	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose 95 % Non-fibrous	NA	Non- Asbestos Containing
648437	AOC2A-7	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose 95% Non-fibrous	NA ·	Non- Asbestos Containing

NOTE: 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

(b) (4)

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LABID # DE 004 ED LABOR A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 11 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

Date Sampled: Sampled By:

5/13/10 CLIENT

Date Analyzed: 8/10/10

Sam	ple ID	Client-S	upplied D	ata	Analytic	al Data	Re	ported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	Components
648438	AOC1A(689) 70-2	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose 95 % Non-fibrous	NA	Non- Asbestos Containing
648439	AOC2A-15	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	10 % Cellulose	NA	Non- Asbestos Containing
							90 % Non-fibrous		
648440	AOC2A-13	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose 95 % Non-fibrous	NA	Non- Asbestos Containing
		PORT DEPOSIT-	•				95 % Non-tiprous		
648441	AOC2A-35	NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		
648442	AOC2A-37	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		

NOTEM Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE:2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U,S, government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.







A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.F.: E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 12 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date: Date Sampled:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN

Sampled By: CLIENT Date Analyzed:

8/10/10

5/27/10

Sam	ole ID	Client-S	upplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents	
648443	TG4-12	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
		PORT DEPOSIT-					97 76 11011-1101009			
648444	TG10-4	NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
							97 % Non-fibrous		Jonannig	
648445	TG1-14	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
							97 % Non-fibrous			
648446	TG2-2	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	<1 % Chrysotile	Non- Asbestos Containing	
							97 % Non-fibrous		• • • • • • • • • • • • • • • • • • •	
648447	AOC45A-10	PORT DEPOSIT- NTCB 3	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
							97 % Non-fibrous			

Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LABID # DE 004 A.I.H.A. /NLLAP AIHA #100448 NVLAP #101032

Page 13 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Sampled:

Date Analyzed:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

CLIENT Sampled By:

8/10/10

5/13/10

Sample ID		Client-Supplied Data			Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents	
648448	FR104-7	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing	
		DODT DEDOCIT					97 % Non-fibrous			
648450	FR104-9	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose	NΑ	Non- Asbestos Containing	
							95 % Non-fibrous	•	• • • • • • • • • • • • • • • • • • • •	
648451	FR45C-43	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
							97 % Non-fibrous			
648452	FR45C-25	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	<1 % Chrysotile	Non- Asbestos Containing	
							97 % Non-fibrous		Comanning	
648454	AOC2A-6	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	

Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 ED LAND A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 14 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Sampled:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN

Sampled By: Date Analyzed: 8/10/10

5/11/10 CLIENT

Sample ID		Client-S	Client-Supplied Data			al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Compo	nents	
049455	40004.00	PORT DEPOSIT- NTCB	Soil	N1/A	·	BROWN			No.	
648455	AOC2A-33			N/A	Firm		3 % Cellulose	NA .	Non-	

Sample#	Sample #	Location	Type	Friable?	Texture	Color	Asbestiform Components	Asbestiform C	components
648455	AOC2A-33	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA NA	Non-
					1 11111		97 % Non-fibrous		Asbestos Containing
		PORT DEPOSIT- NTCB	Soil			222			
648456	AOC2A-11	14105		N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		
		PORT DEPOSIT- NTCB	Soil			RED			
648457	AOC35-9	,,,,,,,		N/A	Firm	KED	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		Containing
		PORT DEPOSIT- NTCB	Soil			BROWN			
648458	AOC35-24		•	N/A	Firm		2 % Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		
		PORT DEPOSIT- NTCB	Soil			BROWN			
648459	AOC35-5			N/A	Firm	BICOVIA	5% Cellulose	NA .	Non- Asbestos Containing
							95 % Non-fibrous		_

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination. Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles.

Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.



A Certified MBE Company
Delaware Industrial Park, 6 Garfield Way
Newark, DE 19713-5817
Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004

Bryloomewat Lead
A.I.H.A. /NLLAP
Bryloomewat Lead
A Industrial Hygiene
Soe gibology on
(referring)
NVLAP
#101032

CERTIFICATE OF PLM ANALYSIS

Page 15 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Sampled:

8/12/2010

Sampling Data

BLI Project #:

L446705

Project Name:

EA ENGINEERING-WALK-IN

Sampled By: CLI

5/27/10 CLIENT

Date Analyzed: 8/10/10

			applied Da	ata	Allalytic	al Data	176	ported Results	
	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Co	omponents
648461	TG4-5	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648462	F-16	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose	NA	Non- Asbestos Containing
648463 AC	OC28-33	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose	NA .	Non- Asbestos Containing
							95 % Non-fibrous		
648464 AC	OC28-19	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose	NA	Non- Asbestos Containing
							95 % Non-fibrous		oo,naming
648465 A	AOC28-4	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	10 % Cellulose	NA	Non- Asbestos Containing
							90 % Non-fibrous	•	J

NOTE1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

(b) (4)

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

* Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three

samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

* Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles.

Defininitive results can be obtained by TEM analysis.







A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 ED LAND A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 16 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project#: L446705

Project Name: EA ENGINEERING-WALK-IN

Date Sampled: Sampled By:

5/18/10 CLIENT

Date Analyzed: 8/10/10

Sam	ple ID	Client-S	upplied D	ata	Analytic	al Data	Re	ported Result	S
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	components
648466	AOC28-24	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
648467	AOC28-34	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose	NA	Non- Asbestos Containing
		PORT DEPOSIT-					95 % Non-fibrous		
648468	AOC28-20	NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		
648469	AOC28-13	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose	NA	Non- Asbestos Containing
							95 % Non-fibrous		Containing
648470	AOC28-32	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		

Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.







A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com

E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 17 of 17

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/12/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENG!NEERING-WALK-IN

Date Sampled: Sampled By:

5/18/10 CLIENT

Date Analyzed:

8/10/10

Samı	ple ID	Client-S	upplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	estiform Asbestiform		
648471	AOC28-14	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	10 % Cellulose	NA	Non- Asbestos Containing	
							90 % Non-fibrous			
648472	AOC28-35	PORT DEPOSIT- NTCB	Soil	N/A		BROWN			Non-	
					Firm		10 % Cellulose	NA	Asbestos Containing	
							90 % Non-fibrous			
040470	4000 #	PORT DEPOSIT- NTCB	Soil	NICA		BROWN			N	
648473	AO28-5			N/A	Firm		5% Cellulose	NA	Non- Asbestos Containing	
							95 % Non-fibrous		· · · · · · · · · · · · · · · · ·	

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.

A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

Page 1 of 1

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/18/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN-1462309

Date Sampled:

N/A

Sampled By: Date Analyzed: CLIENT

8/17/10

Sam	ple ID	Client-S	upplied D	ata	Analytic	al Data	Re	eported Resul	ts
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform	Components
656188	AOC28-33	PORT DEPSOIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		
656189	AOC35-29	PORT DEPSOIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing
			·				97 % Non-fibrous		
656190	AOC45-16	PORT DEPSOIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos
							97 % Non-fibrous		Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.


^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.

Page **j** of ${\refleta}$



Delaware Industrial Park
6 Garfield Way, Newark, DE 19713-5817

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com



Dedicated to a Cleaner Envi	TOTAL SIR	Je 1962 Tel. (302	2) 131-3310 Pax. (3)	02) 131-31	04		www.battaenv.com	$\underline{}$	EFA Lau#, DE	.004
Customer Billing Informati	ion	111 110 1	Shipping Infor	mation	-		round Time (TAT)		Other TAT Re	muest :
Oustomer bining intermet	Tel:	410-7714950	, , , -		i —	licroscopy	<u>Chemist</u>	ry	Outor IAI No	чисэт.
	~ ^		□ Picked up by		i	Immediate	☐ 24 Hrs			
Customer Name:	H		Delivered by C		1	24 Hrs	□ 48 Hrs	and the same of th		• •
Billing Address 1: 15L	oveton	Circle	Shipped by Cu	ustomer		72 Hrs	□ 72 Hrs			4670Z
Billing Address 2:	2000 KS, 1	ND 2152			回	5 Days	☐ 5-7 Day	ys L ab P r	roject #: 140	2730°
Send Results To: (b) (4)	fel:	410-379-5/14	Project Name:	_	117	CB	CHARLES HAVE AND A STATE OF THE PROPERTY OF TH	Client P	Project #:	
E-mail: (b) (4)	Fax:	410-771-4204	Project Location	າ:	Port	Deposi	<u>+</u>			
BLI Use Only Sample ID #	Sample	Location/Description	Sample	Volume	Sample	Sample Type	Analytical Type/Method	l Results	Date of	Analyst
		10.51	5/26(10		Area	<u> </u>		,	Analysis 8/10/10	77
648387 TG10-14	NTCR	3/501	(C (C (C ()		ļ	50:1	Asbestos	MAD	8/10/10	141
1 388 F-69°			5/27/10		annovariation of the state of t			INAO		
389 F-65	Access to the Spanning of the	A CONTRACTOR OF THE CONTRACTOR	5/26/10	<u> </u>	Ī			NAO		
390 TG4-6			5727/10 0845	<u> </u>				1,00		
391 F-8		,	5/27/10 1005	<u>† </u>	Š			MAD	,	
392 TG 12-2		4433344	5/27/10				**************************************	IVAD		
393 TG10-9			5/20/10 0935					VAO		
394 F-40			5/26/10					TUAD		
395 F-47		Distribution of the section of the s	5/26/10		<u> </u>			TUAT		
# 396 TG8-14	1 000		5/36/10 5/36/10 1015			-		TWAD		
Sample Relinquished by:	(4)			Time:	()(9-	<u> </u>	<u> </u>			
Sample Received by:		Date: Date:	6/16/10	Time:	<u>170c</u>		Jse Only		nod of Payment ash Cashier:	
Sample Received by:	-	Date:	DITTIO	Time:	1000	Are sail below.	mples accepted? If not, please	Ovbiett, —	sa/Master Card/Disco	over
Sample Received by:		Date:		- Time: —		🕍 Ye	s No Received	_	oney Order	7401
Customer Special Request/Co	omments (if a						ation/Comment:		urchase Order#	
		pp.1100-1-0/1								
							INVOICE	Unit Pr	rice/Quote:	
							MAN	Total F	Payment:	
		<u>:</u> :				<u>_</u>	**************************************	Other:		
BLI Use Only							at of Results Reported		plus customer COC	
	I in by:	<u></u> Date of Logi	in: <u>6/18/10</u>	Time:	1720		is COC, customer COC and BL			
Lab Comment:						Report	·	Date:	Tíme:	
						Via: □ Ve	☐ Fax ☐ Phone rbal Person Contacted	E-mail:		
						 ∨6	inai teison contacted			


Page Z of 9



A Certified MBE Company 6 Garfie Dedicated to a Cleaner Environment Since 1982 Tel: (30

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com



Billing Address 1: 15 Love ton Circle Shipped by Customer 12 Hrs 12 Hrs	16-705 6230
Customer Name: EA	16-705 10230
Billing Address 1: 15 Loveton Circle Shipped by Customer 72 Hrs	630 6330
billing Address 1. 17 LOVEINT CITUE	<u>6230</u>
Billing Address 2: SporkS, MD 21152 Send Results To: 10 (4) (4) (4) (5) (4) (6) (7) (7) (7) (7) (7) (7) (7) (7) (7) (7	
The state of the s	
Sample Sample Date of	A b t
BLI Use Only Sample ID# Sample Location/Description Date/Time Volume Area Sample Type Analytical Type/Metriod Results Analysis	Analyst
48397 TG8-8 NTCB/SOIT 5/26/10 SOIT Asbestos NAD 8/10/10	丁(
1398 TG9-2 5/26/10 NAD 1	
399 F-76 5/27/10 IMAD	
-20 5/au/0 1/AD	
5/26/10	
1335 5/26/10	0
402 F-51 1430 NAD	
1140 1 36 1 1440 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
404 TG8-9 512 GID NAO	
405 TG4-14 5/27/10 NAD	
1 400 TG4-11 (b) (4) VAD V	
Sample Relinquished by: / Date: 0/(6/60 Time: (700 BLI Use Only Method of Payment	
Sample Received by: Date:	
Sample Relinquished by: Date: Time: below. Usa/Master Card/Disc	over
Sample Received by: Date: Time: Yes No Received on Ice Money Order	
Customer Special Request/Comments (if applicable):	
Unit Price/Quote:	
Total Payment:	
Other:	
BLI Use Only Format of Results Reported: This COC plus customer COC	
Logged in by: 680 Date of Login: 680 Time: 720 This COC, customer COC and BLI certificate Reported by: Date: Time:	
Lab Comment:	
☐ Verbal Person Contacted:	



Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817

E-mail: battaenv@battaenv.com Weh: http://www.battaenv.com

NV(A) NVLAP # 101032 EPA Lab#: DE004

Dedicated to a Cleaner Envi	ronment Since 1982 Tel: (30)	2) /3/-33/6 Fax: (30	12) 131-31	04			.battaettv.com		21.77.200.17.00	
Customer Pilling Informat	ion	Shipping Inform	mation				nd Time (TAT)		Other TAT Re	quest :
Customer Billing Informat	ion Tel: 410-771-4957	O ourbbing innou	Hation	_	licrosc		Chemistry			•
<i></i> .	•	Picked up by	BLI		Immed	iate	☐ 24 Hrs		mian halani a sa a a a a a a a a a a a a a a a a a	
Customer Name: EA		Delivered by C	ustomer		24 Hrs		☐ 48 Hrs			41,765
	eton Circle	Shipped by Cu	stomer		72 Hrs		□ 72 Hrs			
	s. MD 21152		_		5 Days	;	☐ 5-7 Days	Lab P	roject #: <u>၂</u> ၂	46765 6230
Send Results To: (b) (4)	DI: 410-329-5114	Project Name:	NT	CB -				Client	Project #:	
E-mail: (b) (4)	Fax: 410-771-4204	Project Location	Por	+ Deo	Sit					
		Sample		Sample	Sample	Tuna An	alytical Type/Method	Results	Date of	Analyst
BLI Use Only Sample ID #	Sample Location/Description	Date/Time	Volume	Area	Sample				Analysis	l
648407 TG8-5	NTCB/soil	5/26/10 1045		<u> </u>	Soi	1 A	sbestos	NHD	8/19/10	5.
408 A0C1a(189)3-02	 	5/13/10 1105						NRO		[
409 A0C1i-8		5/10/10						NAO		
410 ACC1C-21		5/10/10						MAC		
41 ACC1C-4		5/10/10						MAD		
412 ACC 450-58		5/14/10						NAO		
U13 40C 45a-39		57/3/10						NAD		
44 40C45a-33		5714/1035	···					NAC	>	
415 AOC4601-25	**1.**	5/13/10 1400				,		MAD		
J 416 A0C450-76	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	5/13/10			† W			IVAO		
Sample Relinquished by:	(4) Date:	6/11/1/10	Time:	170	0	BLI Use	Only	Met	hod of Payment	
Sample Received by:	Date:	6/24/17/10	Time:	1055			accepted? If not, please ex		-	
Sample Relinquished by:	Date:		Time:			below.	,		/isa/Master Card/Disc	cover
Sample Received by:	Date:	All and a second	Time:			Yes [☐ No ☐ Received or	n Ice 🔲 N	Money Order	
Customer Special Request/C	omments (if applicable):					Explanation	Comment:	□ F	Purchase Order#	
Одологиот организация	,							1—	Check #	
		•				that	OUF-	1	Price/Quote:	
						(, 20	-	Othe	Payment:	
BLI Use Only					-	Format c	f Results Reported:			· · · · · · · · · · · · · · · · · · ·
Logged	d in by: BM Date of Lo	gin: 6(8(10	Time:	1720		☐ This CC	OC, customer COC and BLI	certificate		:
Lab Comment:	-					Reported by		Date	e: Time:	
		•				Via: □ F	ax Phone	E-mail:		





A Certified MBE Company

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

NVLAP # 101032 AIHA/NLLAP # 100448 EPA Lab#: DE004

Customer Billing Informatio	n	Shipping Inform	nation		Turn /	Around Time (TAT)		Other TAT Re	auloet :
Customer Banning anormatio	Tel: 410-771-4950	,		<u> </u>	icroscopy	<u>Chem</u>		`	Mier IAI IX	squest.
		□ Picked up by			Immediate	□ 24	Hrs			
Customer Name: EA		Delivered by Co			24 Hrs	□ 48	Hrs) E meetings diller
Billing Address 1: 15 LOV	etan Circle	Shipped by Cus	stomer		72 Hrs	72	Hrs			46705
Billing Address 2: Source	MD AIISO		A 1 T	-/ 12 🔟	5 Days	5 -7	Days	Lab Pro	ject#: 146	12504
Send Results To: (b) (4)	H: 410-324-5114	Project Name:	NI	45				Client Pr	oject#:	
E-mail (b) (4)	Fax: 410-7-71-4204	Project Location:	PO(+	Deposi	+					
BLI Use Only Sample ID #	Sample Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analytical Type/Me	thod	Results	Date of Analysis	Analyst
4841 Aa3-23	N7CB/Soil	5/12/10			50.1	Asbosto	? > /	WAD	81/0/10	57
148 A0C14-2		5/14/10				<u></u>		MAD		
1 419 AOC14-3		হা।ধাত						(7. d/g/		
420 AOC 35-26		5/17/10						JAO		<u> </u>
421 AOC 35-21		5/17/10					1	<u>/AD</u>		
422 ACC 35-30		2/12/10					N	(AD)		
423 A0C35.32		5/18/10					1	NAD		
424 A035.27		5/17/10						SAO		
425 AOC 35-8		ड मिन्निड १०५								
U 426 ADC 35-11/1	o) (4)	5/17/10			U			WAD		1
Sample Relinquished by:	Date:	6/16/10	Time:	1700) BLI	Use Only		Metho	d of Paymen	
Sample Received by:	Date:	6-1-1	Time:	1055		amples accepted? If not, ple	ease explain			
Sample Relinquished by:	Date:		Time:		below	•		_	a/Master Card/Disc	over
Sample Received by:	Date:		Time:			nation/Comment:	eived on Ice		ney Order	
Customer Special Request/Cor	nments (if applicable):				Expia	nadon/Comment:		☐ Che	chase Order#	
						Sec. 12		I—	:e/Quote:	
					1 1	(NVOICE		Total Pa	yment:	
								Other:		
BLI Use Only		11 01 0	· · · - ·		1 1	nat of Results Repo			us customer COC	
	n by:BMDate of Logi	in: 6/18/10	Time:	<u> </u>		his COC, customer COC ar	nd BLI certific			
Lab Comment:						ted by:	ne 🗖	Date: E-mail:	Time:	
					VIA:			E-mail:		····

battaLABORATORIES

CHAIN OF CUSTODY

Page 5 of 9

NV(AP NVLAP # 101032



AIHA/NLLAP # 100448

AIHA/NLLAP # 1004 EPA Lab#: DE004

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

Customer Billing Informat	ion lus lus	Shipping Inform	mation		Turn	Around Time (TAT)		Other TAT Re	naunet :
Customer Bining intormat	Tel: 410-771-495		nauon	/ <u>N</u>	licroscopy	<u>Chemistr</u>	ן אַ	Other IAT N	equest.
		Picked up by	BLI		immediate	☐ 24 Hrs			
Customer Name: EA		Delivered by C	ustomer		24 Hrs	☐ 48 Hrs			
Billing Address 1: 15 Lin	leton Circle	Shipped by Cu	stomer		72 Hrs	☐ 72 Hrs			49702
	ks. MD 21152	•		M	5 Days	□ 5-7 Day	s Lab Pı	roject#: 14	6230
Send Results To:(b) (4)	Tel: 410-329-5114	Project Name:	NIT	(R 🗀				Project #:	40,00
E-mail; (b) (4)	Fax: 410-771-4204	Project Location	· Pod	Den	sit-				······································
BLI Use Only Sample ID#	Sample Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analytical Type/Method	Results	Date of Analysis	Analyst
648427 163-17	NTCB/soil	5/24/10			soil	Ashestos	MAD	8/10/10	JI
1 428 167-5	·	5/25/10				/	MAD		
429 TG5-9		5/25/10	***				NAD		
430 AU3-38		5/13/18					WAD		
431 AC3-49		5/12/10					C(7-chr))	
432 AUC3-29		5/1348			}	217-	AAH)	Ethry	
433 AX 3-11		5/11/10					MAP		
434 AU3-6		5KB					MAD	i I	
435 AOC 3-34		5/6//0					WÁC		
1 436 AOC3-16	0) (4)	5/12/10			V	V	MAO	J	V
Sample Relinquished by:	Date:	6/16/10	Time:	[700	BLI	Use Only	Meth	od of Paymen	t
Sample Received by:	Date:	6/17/16	Time:	1055		amples accepted? If not, please e	-		
Sample Relinquished by:	Date:	·	Time:	·	below	•		sa/Master Card/Disc	cover
Sample Received by:	Date:		Time:		1 '	es No Received	onice Mo	oney Order	
Customer Special Request/C	omments (if applicable):				Expla	nation/Comment:	i—	urchase Order#	
		•				INVO (CE	☐ Ch		
						(114.4.4.	1	rice/Quote:	
							Other:	Payment:	
BLI Use Only					Forr	nat of Results Reported			
Logged	l in by: B 🖂 Date of Log	gin: 618/4	Time:	(720)	_ 🗖 🗆 т	his COC, customer COC and BL	certificate		
Lab Comment:					Repor	ted by:	Date:	Time:	
					1 1	☐ Fax ☐ Phone	E-mail:		
						erbal Person Contacted:			

Page & of 9

Datta LABORATORIES

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com NVLAP # 101032

EPA Lab#: DE004

Customer Billing Informat	tion	Shipping Infor	mation	puniona	Turn A	round Time (TAT)		Other TAT Re	aucet :
odstoffier blinking intofficat	Tel: <u>410-771-495</u> 0	• • •		<u> </u>	licroscopy	Chemistry		Other FATRE	quest.
~ l	<u> </u>	☐ Picked up by	BLI		Immediate	□ 24 Hrs			
Customer Name: <u>LA</u>		Delivered by C			24 Hrs	□ 48 Hrs			1/11
Billing Address 1: 15 Lo	vetonCircle	Shipped by Cu	ustomer		72 Hrs	☐ 72 Hrs			ktr-102
Billing Address 2: Soc.	rks, MD, 21152			_ 145	5 Days	☐ 5-7 Days	Lab Pr	roject#: 1년(<u>6230</u> 9
Send Results To(b) (4)	el: 410-329-5714	Project Name:	N	ICB_			 Client F	Project #:	
E-mail: (b) (4)	Fax: 410-771-4204	Project Location	" Roc	- Depo	75.T			 	
BLI Use Only Sample ID #	Sample Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analytical Type/Method	Results	Date of Analysis	Analyst
698437 AOC DA-7	NTCB/soil	5/10/10			50]	Asbestos	NAD	8/19/10	51
1 438 ACC 1A (689) 70-3		5/13/10					NAO	1	1
439 AO(2A-15		5/W10 0920					NAO		
440 AOCDA-13		5/10/10		-			NAD		
441 AOC2A-35		5/11/10		**************************************			MAD		
442 AOC2A-37		5/11/10		<u></u> , , ,			LAD		
443 TG4-12		5/27/19	·				MAO		
444 7610-4		5/26/10					NAD		
445 TG1-14	***	5/25/10					WAD	>	
446 TG 2-2		5/25/10			1		< 17-Ch	W T	1
Sample Relinquished by:	Date:	6/11/10	Time:	170	() BLIU	se Only	Meth	od of Payment	
Sample Received by:	Date:	uhlio	Time:	1055	-	nples accepted? If not, please exp		-	
Sample Relinquished by:	Date:	A	Time:		below.		☐ Vi	sa/Master Card/Disc	over
Sample Received by:	Date:		Time:		🗘(`Ye	s 🔲 No 🐪 Received on	Ice 🔲 Mo	oney Order	
Customer Special Request/C	omments (if applicable):				Éxplana	ation/Comment:	□ Pu	rchase Order#	
					 			eck#	
		1.				NVOICE	Unit Pr	ice/Quote:	
						,	I	'ayment:	
					━┤ /└──		Other:		
BLI Use Only	Links And Andrews	. Help		d rooms		at of Results Reported:		olus customer COC	
	l in by: <u>Riv</u> Date of Logir	n: 6/18/10	i ime:	(720		s COC, customer COC and BLI co			1
Lab Comment:					Reporte	□ Fax □ Phone	Date:	Time:	
					V a. Ve		<u> </u>		



Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

NVLAP # 101032 AIHA/NLLAP # 100448

EPA Lab#: DE004

			Chinalan Info	matic =		Turn A	round Time (TAT)		Other TAT Re	quest:
Customer B	Billing Informat	ion Tel: 410-771-4951	Suibbing intori	паноп	M	licroscopy	<u>Chemistry</u>		Julio IAI No	74006,
	· ·		☐ Picked up by	BLI		Immediate	□ 24 Hrs			
Customer Nar	me: EA		Delivered by C	ustomer		24 Hrs	□ 48 Hrs		, (LI	46705
Billing Addres	s 1: 15/04	eton circle	Shipped by Cu	istomer		72 Hrs	☐ 72 Hrs			
Billing Addres	s 2: Souck	S. MA 21152		4.5.		∕5 Days	☐ 5-7 Days			<u>6230</u> 9
Send Results	_{s T} (b) (4)	Tel: 410-329-5714	Project Name:	NI	<u>CR</u>			Client I	Project #:	
E-mail: (b) (4)		Fax: 410-77-4204	Project Location	:: <u>Port</u>	Depo	sit				
BLI Use Only	Sample ID #	Sample Location/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analytical Type/Method	Results	Analysis	Analyst
6484477	40CHEU-103	NTCB/Soil	5/14/19			soil	A shestos	NAD	8/19/10	J 1
	FR104-7		5/13/10 1405					MAD	>	4
449	FR 104-3		5/13/10					7/25		
450	FR 104-9		5/13/10					NAC		
451	FR 45c-43		5/12/10					INVO		
452	FR45c-25		5/17/10					MAO		
483	FR 45C-16		5/11/10							
	AOCJA-6		5/10/10					WAD		-
485	A0C24-33	100	5 /11/10					MAD	<u> </u>	
J 456	ACCAA-11	0) (4)	5/10/10				V	MAC	> V	V
Sample Relin	quished by: 🖊	Date:	4/16/10	Time:	170	 -	Use Only	,	hod of Payment	t
Sample Rece	***************************************	Date:	6/11/16	. Time: Time:	1055	Are sa	imples accepted? If not, please exp		Cash Cashier: /isa/Master Card/Disc	cover
Sample Relin Sample Rece	·	Date:		Time: —			es 🔲 No 🔝 Received or	_	Money Order	
,		Comments (if applicable):					nation/Comment:		Purchase Order#	
Customer Sp	beciai Requesiic	onnents (n applicable).							Check#	
							le Comme	1	Price/Quote:	
							INVOICE	Othe	Payment:	
DI 111 O-1						Forn	nat of Results Reported:			
BLI Use Only		d in by: Date of Log	in: 41810	Time:	(720)		his COC, customer COC and BLI c			
Lab Comme			, <u> </u>			1 1 '	ted by:	Date		
			-			Via:	Fax Phone erbal Person Contacted:	E-mail:		
1						"" "	andi reson contacted.			



Delaware Industrial Park



AIHA/NLLAP # 100448


6 Garfield Way, Newark, DE 19713-5817 E-mail: battaenv@battaenv.com EPA Lab#: DE004 Web: http://www.battaenv.com Dedicated to a Cleaner Environment Since 1982 Tel: (302) 737-3376 Fax: (302) 737-5764 Turn Around Time (TAT) 410-771-4958 Shipping Information Other TAT Request: **Customer Billing Information** Microscopy Chemistry Immediate □ 24 Hrs ☐ Picked up by BLI ☐ 48 Hrs ■ Delivered by Customer ☐ 24 Hrs Customer Name: Shipped by Customer 72 Hrs □ 72 Hrs Billing Address 1: ₫ 5 Days Lab Project #: 14623 □ 5-7 Days Billing Address 2: Client Project #: Project Name: Send Results To(b) -771-400/Project Location: E-mail: Sample Sample Analyst Analytical Type/Method Results Volume Sample Type Sample Location/Description **BLI Use Only** Sample ID # Analysis Date/Time 5/14/10 asbestos 501 648457 AUC 35-24 489 060 46 462 5/18/10 463 464 465 **Method of Payment** Time: **BLI Use Only** Sample Relinquished by: Date: Cash Date: 616 Time: Are samples accepted? If not, please explain Sample Received by: Time: Date: Sample Relinguished by: Ĭ⊠ Yes 🔲 No Received on Ice Money Order Time: Date: Sample Received by: Explanation/Comment: Purchase Order# Customer Special Request/Comments (if applicable): Check # INVOICE Unit Price/Quote: Total Payment: Other: **BLI Use Only** Date of Login: 6/18/10 Time: 1720 ☐ This COC, customer COC and BLI certificate Logged in by: Reported by: Lab Comment: Via: 🔲 Fax ☐ Phone

☐ Verbal

Person Contacted:



NVLAP # 101032



Dedicated to a Cleaner Environment, Since 1982

Lab Comment:

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

Via: 🗖 Fax

Verbal

Turn Around Time (TAT)	_
Customer Billing Information Tel: 410-141-495 Shipping Information Turn Around Time (TAT) Microscopy Chemistry Other TAT	Request :
□ Picked up by BLI □ Immediate □ 24 Hrs	
	(,
Billing Address 1: 15 Overland Civil Shipped by Customer 72 Hrs	446102
Billing Address 2: Sources MD 2152	446705 46230
Billing Address 2: Society Strain Address 2:	
E-mail: (b) (4) Project Location: Port Depost	
Sample Sample Date of	Analyst
BLI Use Only Sample ID # Sample Location/Description Date/Time Volume Area Sample Type Analytical Type/Intention Results Analys	S
647467 ADCX-34 NTCB/Soil 5/18/10 Soil Asbestes MAD 8/19	6 JT
1 468 AGC 28-20 1	
469 Dry 28-13	
470 A0C28-32	
471 ADC 28-H NAD	
472 Box 78-35 / MAD	
473 A028-5 / V V V V NAD V	
656188 A0C28-33	
189 Acc35-29 1	
190 Ace45-16(b)(4)	
Sample Relinquished by: / Date: //O BLI Use Only Method of Paym	ent
Sample Received by: Are samples accepted? If not, please explain Cash Cash	
Sample Relinquished by: Date: Time: below. Usa/Master Card Seconds Received by: Date: Time: Date: Time: Date: D	Discover
Sample Received by:	
Customer Special Request/Comments (if applicable):	
Unit Price/Quote:	
(NVO)CE Total Payment:	
Other:	
BLI Use Only Format of Results Reported: This COC plus customer C	OC
Logged in by: BY Date of Login: 6 (8)0 Time: 1720 This COC, customer COC and BLI certificate Reported by: Date: 1	me:

E-mail:

Phone

Person Contacted:

(b) (4)

From:

(b) (4)

Sent:

Wednesday, August 18, 2010 10:35 AM

To:

(b) (4)

Cc:

Bo Li

Subject: Sample Labeling Clarification

.



(b) (4)

Lab Coordinator
Batta Environmental Associates, Inc.
6 Garfield Way
Newark, DE 19713
(302)737-3376
www.battaenv.com







Sampling Data

BL! Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF PLM

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Page 1 of 4 8/13/2010

Report Date:

Date Sampled: 4/16/10 Sampled By: CLIENT

Date Analyzed: 8/13/10

Sam	ole ID	Client-S	upplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components	
652188	R-177	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
		DODE DEDOCIE					97 % Non-fibrous			
652189	NR-61	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing	
•							97 % Non-fibrous		Containing	
652190	R-75	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
							97 % Non-fibrous			
652191	NR-43	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing	
	•						98 % Non-fibrous		Containing	
652192	1A-6	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose	NA	Non- Asbestos Containing	
							97 % Non-fibrous			

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



batta LABORATORIES

BATTA LABORATORIES, INC.

A Certified MBE Company
Delaware Industrial Park, 6 Garfield Way
Newark, DE 19713-5817
Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com



CERTIFICATE OF PLM ANALYSIS

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Page 2 of 4

Report Date: Date Sampled: 8/13/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

Sampled By: CL

4/20/10 CLIENT

Date Analyzed: 8/13/10

Samp	ole ID	Client-S	upplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components	
652193	1A-28	PORT DEPOSIT- NTCB	Soil .	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing	
652194	1A-45	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing	
652195	1A-41	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing	
652196	1A-76	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing	
652197	1A-40	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing	

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:



^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

^{*} Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



BATTA LABORATORIES, INC.

A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

ED LABORY OF E.P.A. LABID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

CERTIFICATE OF PLM ANAI

Page 3 of 4

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/13/2010

Sampling Data

BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN

Date Sampled:

4/19/10

Sampled By: Date Analyzed: CLIENT 8/13/10

Sam	ole ID	Client-S	upplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	form Components	
652198	NR-31	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing	
652199	1A-70	PORT DEPOSIT- NTCB	Soil	. N/A -	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing	
652200	1A-75	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	98 % Non-fibrous 2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing	
652201	1A-13	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA .	Non- Asbestos Containing	
652202	1A-74	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3% Cellulose 97% Non-fibrous	NA	Non- Asbestos Containing	

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

Defininitive results can be obtained by TEM analysis.

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. goverment agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination. * Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles.



BATTA LABORATORIES, INC.



A Certified MBE Company
Delaware Industrial Park, 6 Garfield Way
Newark, DE 19713-5817
Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004

AIHA

AIHA

Environmental Lead
8. Industrial Trygiens
See ablietics, rig
for distrib.

NVLAP
#101032

CERTIFICATE OF PLM ANALYSIS

Page 4 of 4

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Date Sampled:

Report Date:

8/13/2010

Sampling Data

BLI Project #: L446705

Project Name:

EA ENGINEERING-WALK-IN

Sampled By:

4/19/10

Date Analyzed:

CLIENT 8/13/10

			Client-Supplied Data Analytical Data					Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components		
652203	1A-32	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing		
652204	1A-67	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing		
652205	R-175	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing		
652206	1A-57	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing		
652207	1A-52	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

(b) (4)

REVIEWED BY:

* Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles.

Defininitive results can be obtained by TEM analysis.

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.



Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

Turn Around Time (TAT)

NVLAP#101032

AlHA/NLLAP # 100448

EPA Lab#: DE004

Customer I	stomer Billing Information Tel: リル・フィーリウミ			Shipping Infor	mation	M	licroscopy	Chemistry		Other TAT Request :		
	·			□ Picked up by	BLI		Immediate	☐ 24 Hrs			<u> </u>	
Customer Na	ime: <u>EA E</u>	Mineerin.		Delivered by C			24 Hrs	☐ 48 Hrs				
Billing Addres	ss 1:15	Loveton C	irde	Shipped by Cu	ıstomer		72 Hrs	☐ 72 Hrs		2/1/		
Billing Addres	ss 2: <u>500</u>	rks MD	21152			미	5 Days	□ 5-7 Days	Lab Proj	ect#: <u>146</u>	2309	
Send Result	s To: (b) (4)	Γel:	410-325-5114	Project Name:		NTO	CB		Client Pro	oject#: عراد	46705	
E-mail: (b) (4	4)	Fax:	410-771-4204	Project Location	:	<u> </u>	- Depos	· +		-		
BLI Use Only	Sample ID #	Sample L	ocation/Description	Sample Date/Time	Volume	Sample Area	Sample Type	Analytical Type/Method	Results	Date of Analysis	Analyst	
652188	R-177	MITCB	150:1	4114110			50:1	As bestos	MAP	8/(3/10	57	
185	Ne-61			4119110					NAD			
190	12-75			4/16/10					NAD			
191	NR-43			416/10					MAD			
192	1A-6			4119110					MAO			
193	1A-28			4/20/10					NAO			
194	JA-45	·		4119110					MAO			
195	1A-41			4170/10					NAO			
196	19-76			4119110					NAO	1		
197	19A-40	0) (4)		415/110				V	WAD	Ψ	U	
Sample Relir	· /		Date:	4/23/10		- 1631) BLI	lse Only		d of Payment		
Sample Rece			Date:		Time:		Are sa below.	mples accepted? If not, please ex	•			
Sample Relin			Date: Date:		Time:		1	s 🔲 No 🔲 Received o		Master Card/Disco	over	
		anamonto (it one			111116.		<u> </u>	ation/Comment:		hase Order#	ļ	
Customer 5	pecial Request/C	omments (if app	ilicable):				l lexpian	ation/Comment.	Chec			
									Unit Price	-		
									Total Pay	ment:		
							▃▋▐└▃		Other:			
BLI Use Onl	у	(b) (4)		-/ -1				at of Results Reported:		s customer COC		
	Logged	l in by: (b) (4)	Date of Log	n: 2 /15/10	Time:	17-0		is COC, customer COC and BLI		T'	j	
Lab Comme	nt:						Report Via:	ed by:	Date:	Time:		
							Ŭ Ve					

CHAIN OF CUSTODY

Page Z of Z

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

NV(A) NVLAP # 101032 AIHA/NLLAP # 100448 EPA Lab#: DE004

Customer E	Billing Informat	71-4950	Shipping Information Mic			Microscopy Chemistry				 0	Other TAT Reques			
		* .	110 1	11 (100	☐ Picked up by	BLI	1 -	Immedia		1 -	24 Hrs			
Customer Na	me: $\overline{\mathcal{L}}A$	Enzineer	.04		Delivered by 0			24 Hrs			1 48 Hrs		***************************************	
Billing Addres	ss 1: 15		Circle		⊡-≲hipped by Cu		1	72 Hrs		i	70 Hrs			
Billing Addres	s 2: 44 A	WKS MD		<u></u>			i	5 Days		I	721115 1 5-7 Days	l ob Droi	H. 111/	~~ DE
Send Results	s To: (b) (4)			29.5114	Project Name:			7C (3	>	***************************************	a J-1 Days	Cliant But	ect#: <u>/</u>	000)
E-maii: (b) (4		L.		71-4704	Project Location		5	1 4-		. 1		Chefft Pro)ject #: <u>/ / /</u>	46 705
BLI Use Only	C				Sample		Sample		7	ろ・・・		 	Date of	.
BLI USE Only	Sample ID #	Sample I	_ocation/[Description	Date/Time	Volume	Area	Sample T	ype	Analytical Typ	pe/Method	Results	Analysis	Analyst
652 198	NR-31	NTCE	3) 5	Soil	498190			501		A 120	5105	MAO	8(13/10	5.7
199	1A-70		1	,	4119160		***************************************				ſ	1000	1	,
250	1A-75				4120110				7			1000		
201	1A-13		t		4/21/10 1025			<u> </u>	1			NAD		
202	10-74	·			7/19/10		-		-	70.30.4		······································		
	A-32				9119110 1240					hastanianianianianiania		MAD		1-1
203					1240						57	MAD		ļ
204	17-67			:	4/11/2/10							NAO		
205	R-175				4/16/10							NAD		
206	1A-57		1/		4/19/10				i		/	WAD		
207	JA-520) (4)			4120110			V				NAD	V	V
Sample Relind				Date:		Time:	630	В	LI Us	se Only			of Payment	<u> </u>
Sample Receiv	· -		/	Date:		Time:				ples accepted? If r	ot, please exp		-	
Sample Reling Sample Receive	· <u> </u>			Date:		Time:		[·	low.			☐ Visa/I	Master Card/Disco	over
	<u> </u>			Date:		Time:		=			Received on	Ice Mone	y Order	
Customer Spe	ecial Request/Co	omments (it app	olicable):					E	planati	tion/Comment:		1	ase Order#	
												Check		
												Unit Price		
												Total Payr Other:	nent;	
BLI Use Only		(b) (4)						= F	orma	t of Results R	eported:	☐ This COC plus	customer COC	
	Logged	in by:		Date of Logi	in: 7/5/co	Time: _	17:37			COC, customer C				
Lab Comment	t:				- · · · · · ·	-			ported	· -		Date:	Time:	
								Via				E-mail:		
								-] Verb	a Person	Contacted:			





Sampling Data


BLI Project #: L446705

Project Name: EA ENGINEERING-WALK-IN-1462309

BATTA LABORATORIES, INC.

A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: <u>battaenv@battaenv.com</u>



CERTIFICATE OF PLM

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Page 1 of 4 8/18/2010

Report Date:

Date Sampled: 4/20/10

Sampled By:

CLIENT

Date Analyzed:

8/18/10

Sam	ole ID	Client-S	upplied D	ata	Analytic	al Data	Reported Results			
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	omponents	
652452	1A-64	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	3 % Cellulose	NA	Non- Asbestos Containing	
652453	1A-27	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	2 % Cellulose	NA	Non- Asbestos Containing	
652454	1A-12	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing	
652455	1A-16	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing	
652456	1A-44	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose 97 % Non-fibrous	NA	Non- Asbestos Containing	

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed. Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP #100448 **NVLAP** #101032

FICATE OF

Report Date:

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Date Sampled:

Date Analyzed:

Page 2 of 4 8/18/2010

Sampling Data

Project Name:

BLI Project #: L446705

EA ENGINEERING-WALK-IN-1462309

4/20/10 Sampled By: CLIENT

8/18/10

Samp	ole ID	Client-Sı	upplied D	ata	Analytic	cal Data	Re	eported Result	5
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform C	components
652457	1A-14	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
652458	1A-17	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	3 % Cellulose	NA	Non- Asbestos Containing
652459	1A-24	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing
652460	1A-3	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5 % Cellulose 95 % Non-fibrous	NA	Non- Asbestos Containing
652461	1A-54	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose 98 % Non-fibrous	NA	Non- Asbestos Containing

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way DE 19713-5817 Newark, Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 A.I.H.A. /NLLAP AIHA #100448 **NVLAP** #101032

ECATEOE

Page 3 of 4

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

8/18/2010

Sampling Data

Project Name:

BLI Project #: L446705

EA ENGINEERING-WALK-IN-1462309

4/19/10 Date Sampled: Sampled By:

CLIENT

Date Analyzed: 8/18/10

Samp	ole ID	Client-Si	Client-Supplied Data			cal Data	Re	eported Result	is
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform (Components
652462	1A-58	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
		PORT DEPOSIT-	Soil				37 70 NOTH HOTOUS		
652463	1A-22	NTCB	0011	N/A	Firm	BROWN	3 % Cellulose	lose NA As	
							97 % Non-fibrous		Containing
652464	1A-46	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN			Non- Asbestos
							98 % Non-fibrous		Containing
652465	1A-12	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN 3 % Cellulose NA		NA	Non- Asbestos Containing
							97 % Non-fibrous	on-fibrous	
652466	1A-66	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment.

^{*} Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination.

Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.





A Certified MBE Company Delaware Industrial Park, 6 Garfield Way Newark, DE 19713-5817 Tel. (302) 737-3376 Fax (302) 737-5764

Web: http://www.battaenv.com E-mail: battaenv@battaenv.com

E.P.A. LAB ID # DE 004 TED LABORD A.I.H.A. /NLLAP #100448 **NVLAP**

#101032

IFICATE OF

Page 4 of 4

Test Method: BATTA SOP in conjuction with EPA 600/R-93/116

Report Date:

Date Analyzed:

8/18/2010

Sampling Data

Project Name:

BLI Project #: L446705

EA ENGINEERING-WALK-IN-1462309

Date Sampled: 4/19/10 Sampled By:

CLIENT 8/18/10

Sample ID Client-Supplied Data **Analytical Data** Reported Results

Oam	סו סונ	Olichi-5	upplied D	ata	Allalytic	ai Data	110	ıs	
Lab Sample#	Client Sample #	Sample Location	Material Type	Friable?	Texture	Color	Non- Asbestiform Components	Asbestiform Components	
652467	1A-71	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	2 % Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		
652468	NR-28	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	5% Cellulose	NA	Non- Asbestos Containing
							95 % Non-fibrous		
652469	R-60	PORT DEPOSIT- NTCB	Soil	N/A	Firm	BROWN	3 % Cellulose	NA	Non- Asbestos Containing
							97 % Non-fibrous		
652470	R-151	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	2 % Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		
652471	1A-59	PORT DEPOSIT- NTCB	Soil	N/A	Firm	TAN	2 % Cellulose	NA	Non- Asbestos Containing
							98 % Non-fibrous		

NOTE 1 Organically-bound, nonfriable material may interfere with the accurate quantification of asbestos. In these cases, the EPA recommends more definitive analysis by a matrix-reduction method (i.e. Chatfield SOP-1988-02, Rev.1).

NOTE 2 Due to limitations of the EPA PLM method, floor tiles may yield false negative (<1%) results by this method. Due to this, the EPA recommends more definitive analysis using analytical electron microscopy.

ANALYST:

^{*} This report does not constitute endorsement by NVLAP and/or any other U.S. government agencies.

^{*} The test data pertain only to the items tested. No assumptions or conclusions should be made to materials or samples not analyzed.

Furthermore, Batta Laboratories, Inc. assumes no responsibility for the accuracy of results influenced by the use of improper collection techniques or equipment. * Due to the general inhomogeneity of asbestos containing materials (ACM), EPA and OSHA have recommended submission of at least three

samples of each type of materials for PLM analysis. Submission of fewer samples may compromise the accuracy of ACM determination. Floor tile samples may yield "false negative" (<1%) asbestos results. There is no EPA approved PLM-analytical method for floor tiles. Defininitive results can be obtained by TEM analysis.



Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

NVLAP # 101032



AIHA/NLLAP # 100448

EPA Lab#: DE004

Customer Billing Information Tel: 910-771-4950					<u>M</u>	Microscopy		nd Time (TAT) <u>Chemistry</u>		Other TAT Request :		
	1-10	1 -	· ·	☐ Picked up by			Immediate		☐ 24 Hrs		ananasiana manja aya kamanan ahalaman ahaaya	
Customer Name: EA Engineering				Delivered by C		1	24 Hrs		48 Hrs			-
Billing Addres	s 1: <u>\</u> 5	Loveten Ci	rde	Shipped by Cu	istomer		72 Hrs		☐ 72 Hrs		2 4 5	
Billing Address 2: Sowks, MD Z1152						☑ 5 Days ☐ 5-7 Day			Lab Project #: 190730			
Send Results To: (b) (4) el: U10-379-5114			Project Name:			NTO	<i>- 13</i>	Client Project #: くらいろう				
E-mail: (b) (4	4)	x: <u>دار</u>	D-771-4204	Project Location	:	<u> </u>	Part T	Depos	<u>, + </u>			
BLI Use Only	Sample ID #	Sample Locat	ion/Description	Sample Date/Time	Volume	Sample Area	Sample Typ	pe Änalyti	cal Type/Method	Results	Date of Analysis	Analyst
652452	1A-64	NTCBI	50:1	1340			50:1	1 AS	bestos	NAD	8/18/10	JT
453	17-27		4	1/20/10						NAC)	
454	1A-12	1		415110						NAT		
455	1A-16			4120110						MAD)	
456	1A-44			4/19/10						(VAD)		
457	19-14			4/20/10						MAD		
458	1A-17		,	4119110						NAD	>	
459	1A-24			9120110						NAD		
4160	1A-3		1	1335						NAD		
7 461	1A-54 (b)	(4)	V	4120116)		V	NAD	, 4	V
Sample Relind			Date:	4/23/10	Time:	630	BL	l Use Only		Metl	hod of Payment	
Sample Recei		U	Date:		Time:				oted? If not, please exp			
Sample Relind	· · · · · · · · · · · · · · · · · · ·		Date:		Time:		belo		C Deschartes		/isa/Master Card/Disc	over
Sample Recei		4.6	Date:		Time:		_ 1_	Yes No			Money Order	
Customer Sp	ecial Request/C	omments (if applica	ble):				Exp	lanation/Comm	nent:	,	Purchase Order# Check #	
										1—	Price/Quote:	
							1 11			i	Payment:	
										Other		
BLI Use Only		(b) (4)							sults Reported: stomer COC and BLI co		plus customer COC	
l - b O	Logged	in by:	Date of Log	in: 7/16/10	Time:	12:40		T !	ā			
Lab Commen	IL.						Via:	oorted by: :	☐ Phone	Date E-mail:	e: Time:	
								Verbal	Person Contacted:			

Page 2 of 2



A Certified MBE Company

Dedicated to a Cleaner Environment Since 1982

Delaware Industrial Park 6 Garfield Way, Newark, DE 19713-5817 Tel: (302) 737-3376 Fax: (302) 737-5764

E-mail: battaenv@battaenv.com Web: http://www.battaenv.com

Turn Around Time (TAT)

NVLAP # 101032

AIHA/NLLAP # 100448

AIHA/NLLAP # 1004 EPA Lab#: DE004

Customer E	Billing Informat	ion Tel: 410	-771-495C				licrosc			Chemistry		other TAT Re	equest :
	n-10	Enineerins	·	☐ Picked up by			Immed			□ 24 Hrs		is and the second se	ediachmentaria e e e e e e e e e e e e e e e e e e e
Customer Na		Delivered by C	□ 24 Hrs			☐ 48 Hrs							
Billing Addres		Shipped by Cu	72 Hrs				□ 72 Hrs		140	1.7210			
Billing Addres					5 Days			☐ 5-7 Days	J.	Lab Project #: 146730			
Send Result	s To: (b) (4)	Tel: 410 2		Project Name:		1010	213				Client Pr	oject #: _ ر د	146700
E-mail: (b) (4	!)	ах: <u>410-</u>	771-4704	Project Location	1: 	test	$\mathbb{D}_{\mathbb{C}}$	av.	sid				
BLI Use Only	Sample ID #	Sample Locatio	n/Description	Sample Date/Time	Volume	Sample Area	Sample	Туре	Analytic	al Type/Method	Results	Date of Analysis	Analyst
652 460	1A-58	NTCB/	50:1	1305			Soi		A	hestos	NAO	8/18/10	77
463	1A-2Z			9/20/10							NAD		
464	1A-46			4116/10					Page and Market Service State of the Service S		MAD		
465	19-12			4121/10					aghaga a Mariad a san an a		MAD		
466	1A-66			4119/10							NAO		
467	19-71			4119110							11/49		
468	MR-28			4/16/10							MAD		
465	R-60		***************************************	4110110							NAD		
470	R-151		4	7/16/10			,	/_		/	NAD		
\$ 471	1A-59	b) (4)		4/20/10			\ \				NAD	Ŭ	
Sample Relin			Date:	4/23/10	Time:	1430			Jse Only			d of Payment	:
Sample Rece Sample Relin			Date: Date:		Time:			Are sar below.	mples accept	ed? If not, please exp		h Cashier: a/Master Card/Disc	over
Sample Rece			Date: _		Time:				s 🔲 No	☐ Received on		ney Order	Over
		omments (if applicabl	e):		-			Explan	ation/Comme	nt:	☐ Pur	chase Order#	
•	•	` .,	•								☐ Che	ck#	
							11				i	e/Quote:	
											Total Pa Other:	yment:	
BLI Use Only	, .						=	Form	at of Res	ults Reported:		us customer COC	
DEI OSE OIII)		in by: (b) (4)	⊃ Date of Log	gin: 7/18/18	Time:	12:20				omer COC and BLI co		,	
Lab Commer		31					Ŭ 	Report	•		Date:	Time:	
									☐ Fax	☐ Phone	E-mail:		
							. I	□ Ve	rhal I	Person Contacted:			